



FA-TS-M12X125 (THREADED SOCKET)

The System

This internally threaded rod is suitable for applications requiring removable eyebolt such as residential balconies or areas with increased trip hazard.

Special Features:

- ✓ Fits removable eyelet M12
- ✓ Comes with 1x button head screw

Uses:

AR-IT epoxy anchor is designed to support a removable eyebolt.

Installation by trained and certified personnel in accordance with AS/NZS 1891.4:2025, AS/NZS 5532:2025, ISO 22846 (2020) and manufacturer's instructions.

Product Warranty:

10 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations.

Important Note:

Failure to supply and/or install proprietary product in accordance with above standards and codes, specifications and instructions voids complete system certification and/or warranty.

Technical Data

Material Used:

316 Stainless Steel

Finish:

Bright

Dimensions:

- ✓ Overall length – 125mm
- ✓ Internal thread – M12
- ✓ External thread – M16
- ✓ Weight – 223 grams

Fixing Details:

Chemset 1 x Hilti HVU2 M16 or injectable equivalent (hole 25 DIA)

Maintenance:

Inspection and load testing required by competent person at intervals not exceeding 12 months as specified in AS 1891.4:2025, and ISO 22846 (2020).

Standards:

AS/NZS 1891.4:2025, AS/NZS 5532:2025
ISO 22846 (2020)