



AA404P PEDESTAL WITH M12 WELDED SWIVEL EYE BOLT

The System

Developed for applications in concrete and steel AA404P Pedestal with M12 Welded swivel eye bolt is designed to withstand a fall arrest load of 15kN. It can be used for a wide range of applications and host structures.

Special Features:

- ✓ 360 degree loading including tension
- ✓ Welded swivel eye bolt
- ✓ Complete traceability
- ✓ High profile design

Uses:

AA404P anchor is designed for industrial rope access (abseiling) and to support a fall arrest load of 15 kN provided a suitable personal shock absorber is used.

It is useful in some applications where the extra height of the anchorage is important and where tensile loading is desirable. Installation by trained and certified personnel in accordance with AS/NZS 1891.4:2025, ISO 22846 (2020) and manufacturer's instructions.

Product Warranty:

10 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations.

Important Note:

Failure to supply and/or install proprietary product in accordance with above standards and codes, specifications and instructions voids complete system certification and/or warranty.

Technical Data

Material Used:

Investment Cast 316 Stainless Steel (Post and the Eye)
316 Stainless Steel (Bolt)

Finish:

Electro polished

Abseil Capacity:

15 kN

Fall Arrest Capacity:

15 kN

Dimensions:

- ✓ Overall height – 160 mm
- ✓ Eye Diameter – 45 mm x 26 mm
- ✓ Weight – 1,650 g

Fixing Details:

3 x Chemical HILTI HVU2 or equivalent M12 (hole 14 DIA)
3 x Through bolt M12 (HOLE 14 DIA)

Maintenance:

Inspection and load testing required by competent person at intervals not exceeding 12 months as specified in AS 1891.4:2025 and ISO 22846 (2020).

Standards:

AS/NZS 1891.4:2025, AS/NZS 5532:2025
ISO 22846 (2020)