



AA404 PEDESTAL

The System

Developed for applications in concrete and steel AA404 Pedestal is used to support a swivel eye bolt or as a static line end anchor point carrier.

Special Features:

- ✓ Unique robust design
- ✓ Complete traceability
- ✓ High profile design

Uses:

AA404 is useful in some applications where the extra height of the anchorage is important such as installations through topping.

Installation by trained and certified personnel in accordance with AS/NZS 1891.4:2025, ISO 22846 (2020) and manufacturer's instructions.

Product Warranty:

10 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations.

Important Note:

Failure to supply and/or install proprietary product in accordance with above standards and codes, specifications and instructions voids complete system certification and/or warranty.

Technical Data

Material Used:

Investment Cast 316 Stainless Steel (Post and the Eye)
316 Stainless Steel (Bolt)

Finish:

Electro polished

Abseil Capacity:

N/A

Fall Arrest Capacity:

N/A

Dimensions:

- ✓ Overall height – 100 mm
- ✓ Weight – 1,240 g

Fixing Details:

- ✓ 3 x Chemical HILTI HVU2 or equivalent M12 (hole 14 DIA)
- ✓ 3 x Through bolt M12 (HOLE 14 DIA)

Maintenance:

Inspection and load testing required by competent person at intervals not exceeding 12 months as specified in AS 1891.4:2025, and ISO 22846 (2020).

Standards:

AS/NZS 1891.4:2025, AS/NZS 5532:2025
ISO 22846 (2020)