



AA406K SWIVEL ANCHOR POINT KIT

The System

Developed mainly for applications in concrete and steel the AA406K anchor point kit features a 360° swivel eye which offers a uniform loading in all directions preventing side loading of a karabiner attachment.

Special Features:

- ✓ 360° swivelling anchor point
- ✓ Used for both fall arrest rope access
- ✓ Kit includes 80mm base plate, M12 x 145mm s/s rod, 1 off M12 nylock nut, 1 off M12 washer, 1 off M12 nylon washer

Uses:

AA406K is designed for use in industrial rope access (abseiling) and to support a fall arrest load of 15 kN in all directions (always in shear) provided a suitable personal shock absorber is used.

Installation by trained and certified personnel in accordance with AS/NZS 1891.4:2025, 22846 (2020) and manufacturer's instructions.

Product Warranty:

10 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations.

Important Note:

Failure to supply and/or install proprietary product in accordance with above standards, specifications and instructions voids complete system certification and/or warranty.

Technical Data

Material Used:

Investment Cast 316 Stainless Steel (eye and base plate)
Grade 316 stainless steel (rod)

Finish:

Electro polish

Abseil Capacity:

15 kN

Fall Arrest Capacity:

15 kN

Dimensions:

- ✓ Length of plate – 95 mm
- ✓ Eye Diameter – 25 mm
- ✓ Base plate diameter – 80 mm
- ✓ Weight of kit – 600 g

Fixing Details:

- ✓ 1 x Chemical HILTI HVU2 M12 or injectable equivalent such as Hilti RE-500 (HOLE 14 DIA)
- ✓ 1x SRA wedge anchor M12x125mm (HOLE 12 DIA)

Maintenance:

Inspection and load testing required by competent person at intervals not exceeding 12 months as specified in AS 1891.4:2025, and ISO 22846 (2020).

Standards:

AS/NZS 1891.4:2025, AS/NZS 5532:2025
ISO 22846 (2020)